

Cyclone (GC)

FEATURES


- 1 Manual rotation (MR) models can be locked into one of four positions
- 2 Short, two-piece rock shield allows use in narrower trenches
- 3 Pin-on carbide teeth rotate while cutting to allow even wear and a better grinding point
- 4 Fully enclosed hydraulic components
- 5 Heavy-duty hydraulic motor and gearbox with a direct drive system ensure solid performance

APPLICATIONS

- Trenching
- Quarry Work
- Demolition
- Tunneling & Mine Work
- Soil Remediation
- Lock & Dam Reconstruction
- Concrete Milling/Resurfacing
- Waterfront Rejuvenation



TRENCHING DETAILS



The Genesis Cyclone can generate a minimum trench width of 32.5" or 40", depending on model.

Metric Specs:

Model Number	Weight	Overall Height	Overall Width	Drum Width	Drum Diameter	Oil Flow	Hydraulic Pressure	Minimum Excavator Wt.
	(kg)	(mm)	(mm)	(mm)	(w/ Teeth)	(lpm)	(bar)	(mt)
GC 550	2,517	1,461	1,207	610	826	230 - 380	310	31
GC 550MR	2,812	1,638	1,207	610	826	230 - 380	310	31
GC 950	3,629	1,778	1,461	889	1,016	340 - 455	310	45
GC 950MR	3,992	1,956	1,461	889	1,016	340 - 455	310	45

All Genesis "MR" model Cyclones feature manual rotation capability.

All Genesis Cyclones are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.