




Demolition Recycler (GDR)

FEATURES



- 1 Reverse-mounted cylinder protects cylinder rod from debris
- 2 Tight fit between the cylinder, body and upper jaw minimizes the risk of debris damaging internal components
- 3 360° rotation comes standard with every GDR
- 4 Combination of a large-bore cylinder and a regeneration valve eliminates the need for an intensifier and a complex hydraulic system
- 5 Built with Weldox steel for the best combination of structural strength and wear durability
- 6 Heavy-duty pivot design with recessed end caps provides structural strength and long-term durability
- 7 Indexable blades provide two useable cutting edges
- 8 Extended chin aids in positioning concrete for processing
- 9 Bolt-on teeth and blades reduce maintenance time
- 10 Weld-on tooth and blade pockets greatly improve the ability to maintain the jaws, extending the GDR's useful life
- 11 Extended upper plate aids in positioning concrete for processing

Shear Jaws	Cracker Jaws	Pulverizer Jaws
 <p>APPLICATIONS</p> <ul style="list-style-type: none"> • Concrete Recycling • C&D Processing • Rebar • Demolition 	 <p>APPLICATIONS</p> <ul style="list-style-type: none"> • Demolition • Concrete Recycling • C&D Processing • Rebar 	 <p>APPLICATIONS</p> <ul style="list-style-type: none"> • Demolition • Bridge Demolition • Structural Steel • Rebar • Wire • Aluminum • Copper

Metric Specs:

Model Number	Weight*	Jaw Opening	Jaw Depth	Tip Force at 5000 psi	Typical Reach	Minimum Excavator Wt.
	(kg)	(mm)	(mm)	(kN)	(mm)	Stick Mounted (mt)
GDR 150	1,565	660	635	756	1,930	12
GDR 200	2,495	889	813	1,023	2,311	20
GDR 300	3,583	1,092	991	1,308	2,667	31

*Weight will vary according to specified jaw configuration.

All Genesis Demolition Recyclers are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.