

Versi Pro 07 (GVP 07)



FEATURES

- 1 Each jaw's pivot group stays intact, allowing the use of a press-fit pin design for a stronger, more durable product and making jaw change-outs safe, easy and fast
- 2 360° rotation comes standard with every Versi Pro
- 3 The innovative bracket system accommodates a skid steer quick plate or a mini excavator lug plate change-over in 10 minutes
- 4 Available with full hydraulic or electric over hydraulic. Electric over hydraulic allows for jaw open or close and rotation with one hydraulic circuit.
- 5 Proprietary regeneration valve improves cycle time by up to 33% compared to standard hydraulic systems
- 6 Jaw change-outs in 10 minutes with the coupler-style connection system

APPLICATIONS

- Interior Demolition
- Scrap Processing
- On-site Material Processing and Handling

Skid Steer Bracket



Skid steer mounting bracket option features a traction grip to provide operator safe entry and exit

Shear Jaws

Patented pivot geometry creates peak power for piercing and cutting

Weld-on wear plate and piercing tip

Four-way indexable guide blades and primary blades provide four useable cutting edges



Cracker Jaws

Patented pivot geometry creates peak power when jaws are fully open, where it's most needed to crush concrete



Open relief design allows concrete to pass through lower jaw

Grapple Jaws

Recessed welds are protected from wear, increasing grapple life



Boxed-tine construction creates a very high strength and lightweight grapple – each tine will withstand the full breakout force of the carrier


Replaceable tine tips are abrasion-resistant

Inside radius matches that of a 55-gallon barrel

Wire Cutter Jaws

Designed for non-ferrous wire only

Bolt-on interchangeable cutting blades can be sharpened and are easily replaced



Curved jaw design gathers material deeper into the jaw for maximum cutting power

Unique self-tensioning pivot group maintains optimal blade clearance

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Weight		Minimum Skid Steer Weight
					Boom Mount (lbs.)	Stick Mount (lbs.)	
Shear Jaws	(lbs.)	(ins.)	(ins.)	w/Jaws Installed (ft. ins.)	12,000	16,000	7,000
Cracker Jaws	1,375	11.5	11.5	5' 6"			
Grapple Jaws	1,385	14.5	13	5' 8"			
Wire Cutter Jaws	1,420	32	15.5	5' 11"			
	1,245	10.5	11.5	5' 9"			

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.

The stability of each lift class varies between OEM skid steer and mini excavator models. Please consult with your Genesis salesperson for recommended carrier models. Joystick control packages are available for carriers less equipped.

Patents: genesisattachments.com/products/patents