

# Rebar Processor (GRP)

## FEATURES

- 1 Extra large, heavy-duty pivot group provides durability for increased processing
- 2 Weldable, replaceable lower tusks provide wear-resistant surfaces necessary for rebar bundle separation
- 3 Weldable, replaceable piercing blades work with the lower tusks to sort/separate rebar bundles
- 4 Bolt-on upper jaw side plate provides a replaceable wear surface and protects the jaw
- 5 Weld-on top guard minimizes build-up and maintenance
- 6 Dual AutoGuides maintain proper jaw alignment and extend bearing life



**APPLICATION**  
Rebar Processing

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Wt.	
	(lbs.)	(ins.)	(ins.)		Boom Mount (lbs.)	Stick Mount (lbs.)
<b>GRP 480</b>	11,900	24	26	10' 1"	48,000	90,000

\*Weight includes mounting bracket to attach to excavator.

\*\*Distance is measured from the attachment mounting pivot (boom or stick) forward.

The GRP is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: [genesisattachments.com/products/patents](http://genesisattachments.com/products/patents)