

# Rail Breaker (GRB)

## FEATURES

- 1 Four-blade design reduces jaw wear and maintenance
- 2 Designed to operate up to 5,000 psi
- 3 Hydraulic accumulators reduce shock loading
- 4 Large-bore cylinder produces more power for improved cutting
- 5 Dual direct-drive motors with built-in case drain system provide rotation control and holding power
- 6 Heavy-duty pivot group with flush caps for increased durability
- 7 Deep jaw design for cutting in the center of the blades



**JAW ARMOR**<sup>™</sup>  
COMPATIBLE

## APPLICATIONS

– Rail Processing

## Metric Specs:

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Wt. Boom Mount (mt)	Minimum Excavator Wt. Stick Mount (mt)
	(kg)	(mm)	(mm)	(mm)		
<b>GRB 30</b>	3,130	248	337	2,794	18	25

\*Weight includes mounting bracket to attach to excavator.

\*\*Distance is measured from the attachment mounting pivot (boom or stick) forward.

The GRB is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: [genesisattachments.com/patents](http://genesisattachments.com/patents)