

Rail Breaker (GRB)

FEATURES

- 1 Four-blade design reduces jaw wear and maintenance
- 2 Designed to operate up to 5,000 psi
- 3 Hydraulic accumulators reduce shock loading
- 4 Large-bore cylinder produces more power for improved cutting
- 5 Dual direct-drive motors with built-in case drain system provide rotation control and holding power
- 6 Heavy-duty pivot group with flush caps for increased durability
- 7 Deep jaw design for cutting in the center of the blades



JAW ARMOR[™]
COMPATIBLE

APPLICATIONS

– Rail Processing

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Wt.	Minimum Excavator Wt.
	(lbs.)	(ins.)	(ins.)	(ft. ins.)	Boom Mount (lbs.)	Stick Mount (lbs.)
GRB 30	6,900	9.75	13.25	9' 2"	40,000	55,000

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.

The GRB is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesistattachments.com/patents