

# XT Mobile Shear (GXT)



## FEATURES

- 1 All the power in a shorter, lighter shear with a center of gravity closer to the excavator. Most models mount on smaller size carriers for lower initial investment and hourly operating costs.
- 2 Bolt-on piercing tip encapsulates front of upper jaw, minimizing risk of damage while reducing welding build-up and downtime
- 3 Short primary cutting blades position apex closer to the rear of the jaws and draw material further into the jaws where higher force makes efficient cuts
- 4 Weld-on, replaceable, highly abrasion-resistant steel rhino horn protects front of upper jaw, reducing downtime and welding build-up
- 5 Dual guide blade length matches piercing tip length enabling blades to be shimmed independently to accommodate piercing tip wear
- 6 Improved jaw geometry makes it easier to pick up material and reduces wear from ground contact
- 7 Reverse-mounted hydraulic cylinder shortens shear length and weight while protecting rod from damage
- 8 Remote-mounted hydraulic speed valve improves serviceability and minimizes stress on other critical hydraulic components
- 9 Lower shear height improves visibility while providing superior rigidity and structural integrity

### APPLICATIONS

- Scrap Processing
- Demolition

### Metric Specs:

| Model        | Weight* | Jaw Opening | Jaw Depth | Reach** | Min. Excavator Wt.<br>Boom Mount*** (mt) | Min. Excavator Wt.<br>Stick Mount*** (mt) |
|--------------|---------|-------------|-----------|---------|--|---|
|              | (kg)    | (mm)        | (mm)      | (mm)    |  |   |
| GXT 115****  | 1,406   | 406         | 457       | 1,524   | 7  | 11  |
| GXT 115R**** | 1,610   | 406         | 457       | 2,337   | 8  | 14  |
| GXT 225      | 1,905   | 457         | 508       | 1,727   | 11                                       | 16  |
| GXT 225R     | 2,223   | 457         | 508       | 2,413   | 14                                       | 20  |
| GXT 335      | 2,950   | 584         | 660       | 1,956   | 12                                       | 20  |
| GXT 335R     | 3,311   | 584         | 660       | 2,718   | 17                                       | 30  |
| GXT 445      | 4,309   | 711         | 711       | 2,184   | 18                                       | 34  |
| GXT 445R     | 4,990   | 711         | 711       | 3,073   | 22                                       | 41  |
| GXT 555      | 5,262   | 762         | 762       | 2,438   | 23                                       | 41  |
| GXT 555R     | 5,942   | 762         | 762       | 3,353   | 25                                       | 50  |
| GXT 665      | 5,987   | 813         | 813       | 2,743   | 25                                       | 50  |
| GXT 665R     | 6,668   | 813         | 813       | 3,658   | 31                                       | 54  |
| GXT 775      | 7,031   | 889         | 940       | 2,946   | 31                                       | 61  |
| GXT 775R     | 8,051   | 889         | 940       | 3,962   | 36                                       | 68  |
| GXT 995      | 8,165   | 991         | 1,067     | 3,251   | 36                                       | 77  |
| GXT 995R     | 9,072   | 991         | 1,067     | 4,318   | 45                                       | 82  |
| GXT 1555     | 10,433  | 1,118       | 1,168     | 4,089   | 50                                       | 86  |
| GXT 1555R    | 12,134  | 1,118       | 1,168     | 5,232   | 66                                       | 113                                       |
| GXT 2055     | 14,515  | 1,219       | 1,270     | 4,394   | 66                                       | Contact Factory                           |
| GXT 2055R    | 16,420  | 1,219       | 1,270     | 5,359   | 81                                       | Contact Factory                           |
| GXT 2555     | 22,906  | 1,372       | 1,422     | 4,699   | Contact Factory                          | Contact Factory                           |
| GXT 2555R    | 25,628  | 1,372       | 1,422     | 6,528   | Contact Factory                          | Contact Factory                           |

\*Weight includes mounting bracket to attach to excavator. \*\*Distance is measured from the attachment mounting pivot (boom or stick) forward.  
 \*\*\*2<sup>nd</sup>-member installations that are at or near minimum excavator weight and all 3<sup>rd</sup>-member installations require pre-approval from Genesis.  
 \*\*\*\*The GXT 115 and GXT 115R have a single guide blade. GXT shears are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.  
 Genesis reserves the right to continually make product improvements designed to positively enhance performance.  
 Patents: genesisattachments.com/patents